ABBOGIATION CONNECTING ELECTRONICE INDUSTRIES® INCLUSTRIES®	burn, Illinois, All rights reserved	under both le	his docume vel parts, th	nt is a declaration ne declaration en	on of the subst compasses al	tances withi 1 lower leve	n the manufacture l materials for wh	er listed iten hich the mar	n. Note: if the second se	he item is an as as engineering	sembly with lower responsibility.
IPC Web Site for Information on http://www.ipc.org/IPC-175x	IPC Web Site for Information on IPC-1752 Standard Form Type   http://www.ipc.org/IPC-175x Distribute			Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Materials and I					Informatior	1	
Supplier Information											
npany name* Company unique ID			τ	Unique ID Authority				Response Date*			
onsemi								2023-06-08			
Contact Name	Title - Contact		F	Phone - Contact*				Email - Contact*			
Product-Env-Stewards	Product Enviro Compliance		1	NA				Product-Env-Stewards@onsemi.com			
uthorized Representative* Title - Representative			Phone - Representative*				Email - Representative*				
Product-Env-Stewards	Product Enviro Compliance		NA				Product-Env-Stewards@onsemi.com				
Requester Item Number Mfr Iter	n Number Mfr Item Name	Mfr Item Name		Effective Date	Version	Manuf	Manufacturing Site		ight*	UOM	Unit Type
MC74L	VX257DR2G LOG CMOS QUAD MLTIPL			2023-06-08		PH1	PH1		2.69	mg	Each
Manufacturing Proccess Information										•	·
Terminal Plating / Grid Array Material	Terminal Base Alloy J-STD-020 M		Rating	Peak Proce	Peak Process Body Temperature Max Time a		ax Time at Peak '	k Temperature Number of Reflow Cycles		les	
Matte Tin (Sn) - annealed CU Alloy 1		1		260	C	30	)	seconds	3		
Comments											
evel 1 - maximum time at peak temperature during so	Idering is 10-30 seconds										
For more information regarding material composition	please refer to page 3										

RoHS Material Composition Declaration				Declaration Type *	Detailed
Directive 2015/863/EU amending RoHS Directive 2011/65/EU		nium (Cr6+), Polybro	ominated Biphenyls (PBB), Polybron	dmium and quantity limit of 0.1% by mass (100 minated Diphenyl Ethers (PBDE), and Bis(2-eth	
cadmium, hexavalentchromium, polybrominate contains a RoHS restricted substance inexcess encompass all such components. Supplier certif as of the date that Supplier completes this form Company acknowledges that Supplier may hav independently verified information provided by certification in this paragraph. If the Company a	ed biphenyls and/or polybrominated dip of an applicable quantity limit, please ir ies that it gathered the information it pro- .Supplier acknowledges that Company e relied on informationprovided by othe y others, Supplier agrees that, at a minin and the Supplier enter into a written agre pource of the Supplier's liability and the	henyl ethers (each a " ndicate below which, i ovides in this form us will rely on this certifiers in completing this num, itssuppliers have eement with respect to Company's remedies	RoHS restricted substance") in exce if any, RoHS exemption you believe ing appropriate methods to ensure if ication in determining the complian form, and that Supplier may not have e provided certifications regarding the to the identified part, the terms and co for issues that arise regarding inform	ce of its products with European Union membe	ove. If a homogeneous material within the part er level components, the declaration shall l correct to the best of its knowledge and belief, r state laws that implement the RoHS Directive. wever, in situations where Supplier has not tions are at least as comprehensive as the anty rights and/or remedies provided as part of
RoHS Declaration * 1 - Item(s)	does not contain RoHS restricted substa	ances per the definitio	on above	Supplier Acceptance	* Accepted
Exemption: If the declared item does not con applicable exemptions.	ntain RoHS restricted substances per	the definition above	except for defined RoHS exempti	ons, then select the corresponding response i	n the RoHS Declaration above and choose all
Exemption List Version	EL-2011/534/EU				
Declaration Signature					
Instructions: Complete all of the required fin Requester) and click on Submit Form to have	elds on all pages of this form. Select the form returned to the Requester	he "Accepted" on th	e Supplier Acceptance drop-down	. This will display the signature area. Digital	lly sign the declaration (if required by the
Supplier Digital Signature Ra	stislav Drska	Le			

## Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

sigma range of distribution unless	otherwise noted).							
Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Die	2.73	mg	Supplier	Silicon (Si)	7440-21-3		2.73	mg
Die Attach	4.85	mg		Epoxy resin	proprietary data		0.485	mg
			Supplier	Ethylene dimethacrylate	97-90-5		0.2425	mg
			Supplier	Silver (Ag)	7440-22-4		3.88	mg
			Supplier	Formaldehyde Polymer	9003-36-5		0.2425	mg
Lead Frame	75.92	mg	Supplier	Silver (Ag)	7440-22-4		0.7592	mg
			Supplier	Zinc (Zn)	7440-66-6		0.1518	mg
			Supplier	Iron (Fe)	7439-89-6		1.9739	mg
			Supplier	Copper (Cu)	7440-50-8		73.035	mg
Mold Compound-Black	55.11	mg		Epoxy resin	proprietary data		2.7555	mg
			Supplier	Phenolic Resin	Proprietary Data		1.1022	mg
			Supplier	Ortho Cresol Novolac Resin	29690-82-2		1.3778	mg
			Supplier	Carbon Black (C)	1333-86-4		0.2756	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		49.599	mg
Plating	3.73	mg	Supplier	Tin (Sn)	7440-31-5		3.73	mg
Wire Bond - Au	0.35	mg	Supplier	Gold (Au)	7440-57-5		0.35	mg

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).