


**SIPMOS® Power-Transistor**
**Features**

- P-Channel
- Enhancement mode
- Avalanche rated
- $dv/dt$  rated
- 175°C operating temperature
- Pb-free lead finishing; RoHS compliant

**Product Summary**

$V_{DS}$	-60	V
$R_{DS(on),max}$	0.3	$\Omega$
$I_D$	-8.8	A

**P-TO263-3-2**


Type	Package	Tape and reel information	Marking	Lead free	Packing
SPB08P06P	P-TO263-3-2			Yes	

**Maximum ratings, at  $T_j=25\text{ °C}$ , unless otherwise specified**

Parameter	Symbol	Conditions	Value	Unit
			steady state	
Continuous drain current	$I_D$	$T_A=25\text{ °C}$	-8.8	A
		$T_A=100\text{ °C}$	-6.3	
Pulsed drain current	$I_{D,pulse}$	$T_A=25\text{ °C}$	-35.32	
Avalanche energy, single pulse	$E_{AS}$	$I_D=8.83\text{ A}$ , $R_{GS}=25\ \Omega$	70	mJ
Reverse diode $dv/dt$	$dv/dt$	$I_D=8.83\text{ A}$ , $V_{DS}=48\text{ V}$ , $di/dt=-200\text{ A}/\mu\text{s}$ , $T_{j,max}=175\text{ °C}$	-6	kV/ $\mu\text{s}$
Gate source voltage	$V_{GS}$		$\pm 20$	V
Power dissipation	$P_{tot}$	$T_A=25\text{ °C}$	42	W
Operating and storage temperature	$T_j$ , $T_{stg}$		"-55 ... +175"	$^{\circ}\text{C}$
ESD class				
Soldering temperature			260 $^{\circ}\text{C}$	
IEC climatic category; DIN IEC 68-1			55/150/56	

Parameter	Symbol	Conditions	Values			Unit
			min.	typ.	max.	
<b>Thermal characteristics</b>						
Thermal resistance, junction - case	$R_{thJC}$		-	-	3.6	K/W
Thermal resistance, junction - ambient, leaded	$R_{thJA}$		-	-	62	
SMD version, device on PCB:	$R_{thJA}$	minimal footprint	-	-	62	K/W
		6 cm <sup>2</sup> cooling area <sup>1)</sup>	-	-	40	

**Electrical characteristics**, at  $T_j=25\text{ }^\circ\text{C}$ , unless otherwise specified

**Static characteristics**

Drain-source breakdown voltage	$V_{(BR)DSS}$	$V_{GS}=0\text{ V}, I_D=-250\text{ }\mu\text{A}$	-60	-	-	V
Gate threshold voltage	$V_{GS(th)}$	$V_{DS}=V_{GS}, I_D=-250\text{ }\mu\text{A}$	-2.1	3	-4	
Zero gate voltage drain current	$I_{DSS}$	$V_{DS}=-60\text{ V}, V_{GS}=0\text{ V}, T_j=25\text{ }^\circ\text{C}$	-	-0.1	-1	$\mu\text{A}$
		$V_{DS}=-60\text{ V}, V_{GS}=0\text{ V}, T_j=150\text{ }^\circ\text{C}$	-	-10	-100	
Gate-source leakage current	$I_{GSS}$	$V_{GS}=-20\text{ V}, V_{DS}=0\text{ V}$	-	-10	-100	nA
Drain-source on-state resistance	$R_{DS(on)}$	$V_{GS}=-10\text{ V}, I_D=-6.2\text{ A}$	-	221	300	m $\Omega$
Transconductance	$g_{fs}$	$ V_{DS} >2 I_D R_{DS(on)max}, I_D=-6.2\text{ A}$	2.4	4.8	-	S

<sup>1)</sup> Device on 40mm\*40mm\*1.5mm epoxy PCB FR4 with 6 cm<sup>2</sup> (one layer, 70 $\mu\text{m}$  thick) copper area for drain connection. PCB is vertical without blown air.

Parameter	Symbol	Conditions	Values			Unit
			min.	typ.	max.	

**Dynamic characteristics**

Input capacitance	$C_{iss}$	$V_{GS}=0\text{ V}, V_{DS}=-25\text{ V},$ $f=1\text{ MHz}$	-	335	420	pF
Output capacitance	$C_{oss}$		-	105	135	
Reverse transfer capacitance	$C_{rss}$		-	65	95	
Turn-on delay time	$t_{d(on)}$	$V_{DD}=-30\text{ V}, V_{GS}=-$ $10\text{ V}, I_D=-6.2\text{ A},$ $R_G=6\ \Omega$	-	16	24	ns
Rise time	$t_r$		-	46	69	
Turn-off delay time	$t_{d(off)}$		-	48	72	
Fall time	$t_f$		-	14	21	

**Gate Charge Characteristics**


Gate to source charge	$Q_{gs}$	$V_{DD}=-48\text{ V}, I_D=-8.8\text{ A},$ $V_{GS}=0\text{ to }-10\text{ V}$	-	-1.9	-2.6	nC
Gate to drain charge	$Q_{gd}$		-	-5	-8	
Gate charge total	$Q_g$		-	-10	-13	
Gate plateau voltage	$V_{plateau}$		-	-6	-	V

**Reverse Diode**

Diode continuous forward current	$I_S$	$T_A=25\text{ }^\circ\text{C}$	-	-	-8.8	A
Diode pulse current	$I_{S,pulse}$		-	-	-35.3	
Diode forward voltage	$V_{SD}$	$V_{GS}=0\text{ V}, I_F=-8.83\text{ A},$ $T_j=25\text{ }^\circ\text{C}$	-	-1	-1.55	V
Reverse recovery time	$t_{rr}$	$V_R=30\text{ V}, I_F= I_S ,$ $di_F/dt=100\text{ A}/\mu\text{s}$	-	60	90	ns
Reverse recovery charge	$Q_{rr}$		-	100	150	


**1 Power dissipation**

$$P_{tot} = f(T_A)$$



**2 Drain current**


$$I_D = f(T_A); |V_{GS}| \geq 10 \text{ V}$$



**3 Safe operating area**

$$I_D = f(V_{DS}); T_A = 25 \text{ °C}; D = 0$$


parameter:  $t_p$



**4 Max. transient thermal impedance**

$$Z_{thJA} = f(t_p)$$


parameter:  $D = t_p/T$



**5 Typ. output characteristics**

$$I_D = f(V_{DS}); T_j = 25\text{ }^\circ\text{C}$$


parameter:  $V_{GS}$



**6 Typ. drain-source on resistance**

$$R_{DS(on)} = f(I_D); T_j = 25\text{ }^\circ\text{C}$$


parameter:  $V_{GS}$



**7 Typ. transfer characteristics**


$$I_D = f(V_{GS}); |V_{DS}| > 2|I_D|R_{DS(on)max}$$

parameter:  $T_j$




**8 Typ. forward transconductance**

$$g_{fs} = f(I_D); T_j = 25\text{ }^\circ\text{C}$$




**9 Drain-source on-state resistance**

$R_{DS(on)} = f(T_j); I_D = -6.2 \text{ A}; V_{GS} = -10 \text{ V}$




**10 Typ. gate threshold voltage**

$V_{GS(th)} = f(T_j); V_{GS} = V_{DS}; I_D = -250 \mu\text{A}$



**11 Typ. capacitances**


$C = f(V_{DS}); V_{GS} = 0 \text{ V}; f = 1 \text{ MHz}$



**12 Forward characteristics of reverse diode**

$I_F = f(V_{SD})$


parameter:  $T_j$



**13 Avalanche characteristics**

$I_{AS}=f(t_{AV}); R_{GS}=25 \Omega$


parameter:  $T_{j(start)}$



**14 Typ. gate charge**


$V_{GS}=f(Q_{gate}); I_D=-8.8 \text{ A pulsed}$

parameter:  $V_{DD}$



**15 Drain-source breakdown voltage**

$V_{BR(DSS)}=f(T_j); I_D=-250 \mu\text{A}$



**16 Gate charge waveforms**

**Published by****Infineon Technologies AG****81726 München, Germany****© Infineon Technologies AG 2006.****All Rights Reserved.****Attention please!**

The information given in this data sheet shall in no event be regarded as a guarantee of conditions or characteristics ("Beschaffenheitsgarantie"). With respect to any examples or hints given herein, any typical values stated herein and/or any information regarding the application of the device, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation warranties of non-infringement of intellectual property rights of any third party.

**Information**

For further information on technology, delivery terms and conditions and prices please contact your nearest Infineon Technologies Office ([www.infineon.com](http://www.infineon.com)).

**Warnings**

Due to technical requirements components may contain dangerous substances. For information on the types in question please contact your nearest Infineon Technologies Office.

Infineon Technologies Components may only be used in life-support devices or systems with the express written approval of Infineon Technologies, if a failure of such components can reasonably be expected to cause the failure of that life-support device or system, or to affect the safety or effectiveness of that device or system. Life support devices or systems are intended to be implanted in the human body, or to support and/or maintain and sustain and/or protect human life. If they fail, it is reasonable to assume that the health of the user or other persons may be endangered.